

Performance and Upgrades of the Fermilab Accumulator Stacktail Stochastic Cooling

Paul Derwent, Ed Cullerton, David McGinnis, Ralph Pasquinelli, Ding Sun, David Tinsley
 Fermi National Accelerator Laboratory, P.O. Box 500, Batavia, IL USA 60510-0500

Theory of Stochastic Stacking van der Meer solution:

Desire Constant Flux: $\frac{\partial \psi}{\partial t} = \text{constant}$

Solution: $\frac{\partial \psi}{\partial E} = \frac{\psi}{E_d}$, where E_d characteristic of design $\psi = \psi_0 \exp \frac{E - E_i}{E_d}$

Exponential Density Distribution generated by Exponential Gain Distribution

with theoretical Maximum Flux: $\frac{W|\eta|E_d}{f_0 p \ln \frac{F_{max}}{F_{min}}}$

W bandwidth, F_{max} and F_{min} frequency range

f_0 beam revolution frequency, p beam momentum

η phase slip factor


E_d characteristic gain slope

Abstract:

We report on the performance and planned upgrades to the Fermilab Accumulator Stacktail Stochastic Cooling System. The current system has achieved a maximum flux of 16.5 mA/hour, limited by the input flux of antiprotons. The upgrades are designed to handle flux in excess of 40 mA/hour.



Current System
 Pickups located in region
 of 10 m dispersion
 use pickup response
 relative gain & phase
 to build gain slope
 2-4 GHz sensitivity

1.2 GHz bandwidth
 10 MeV gain slope
 Support ~29.5 mA/hr
 Best Hour: 16.5 mA/hr



Simulation Results:
 Numerical Integration of Fokker-Planck Equation
 including feedback
 Model Pickups, Electronics,
 Kickers over bandwidth

Compared to Single Pulse
 Evolution in Accumulator








Upgrade Design: factor of 2 design margin

Recycler now the final repository for antiprotons

Stage 1: adjust tank positions, gains, and phases to achieve gain slope of 18 MeV
 maximum flux ~55 mA/hour

Stage 2: replace 1/2 of pickups and kickers with 4-6 GHz sensitivity
 maximum flux ~80 mA/hour

Detailed Simulations of Pickup Response Measurements with Stretched Wires



Prototype tank
 being prepared for
 beam measurements
 Fall 05