



ALLIED VAUGHN TEMPLATE		D120 - DVD Silkscreen Imprint (5 & 9)
<p>Helpful Hints</p> <ul style="list-style-type: none"> - Raster images, both grayscale and 4-color process, should be scanned/saved at 300 dpi, at 100% of desired final print size. - Raster art files containing both text and grayscale or 4-color images should be created/saved at 600 dpi, at 100% of desired output size. - Raster artwork containing just text and/or line-art should be created/saved at 1200 dpi, at 100% of desired final print size. - If possible, convert type to outlines or paths in a vector program. - Files that should separate as spot color(s) should not be rasterized or flattened. - A white flood coat is recommended for 4-color process work. - When designing your art, please keep in mind that the clear hub area and mirror band will print differently from the rest of the disc. - Gradient art is NOT recommended - at between 60% and 70%, banding could occur. - Artwork with less than 15% dot fill may not reproduce, and artwork with greater than 85% dot fill may print as a solid. This includes each color in the 4-color process. - Type Sizes: 5 point minimum for one color type, 6 point minimum for type reversed out of one color. We do not recommend reversing type out of two or more colors. If your job requires reversing type out of two or more colors, an 8 point minimum is suggested. 	<p>Graphic File Formats Supported</p> <p>Allied Vaughn prefers Adobe graphics applications for creating and providing art files for labeling and pre-press. Vector art should be provided in .ai, or .eps file formats. Raster art should be provided in .psd, .tif, .jpg or .bmp. Other formats and graphics applications may be supported, contact your Allied Vaughn Representative for details. If you are unable to provide art within these parameters, please inquire about our Graphic Design Services.</p>	<p>CheckList</p> <ul style="list-style-type: none"> <input type="checkbox"/> Template on a separate layer <input type="checkbox"/> Raster images are placed at 100% <input type="checkbox"/> Images are CMYK or Spot (see below) <input type="checkbox"/> Spot (Pantone) colors clearly indicated <input type="checkbox"/> Artwork does NOT bleed <input type="checkbox"/> All printer & screen fonts included with file(s) <input type="checkbox"/> All images included with file(s) <input type="checkbox"/> Laser or color output included <input type="checkbox"/> Spell check & proof read
<p>IMPORTANT: Floodcoats count as a color and will result in additional charges.</p> <p>Please create a color box in your artfile. Each piece of film must separate with it's color designated on the film. (CMYK for process jobs, Pantone number for spot color jobs)</p> <p>Do not send PDF files for film output. Electronic PDF proof files of your artwork will be provided for your approval unless other arrangements are made. Please understand that electronic proofs are good for relative placement and content only - they are not intended as a precise color proofing device.</p> <p>Allied Vaughn prefers to produce the films for each project based on the specific artwork and the regional manufacturing capabilities. This practice should yield the highest level of quality. If you prefer to provide final films, please contact your Allied Vaughn Representative for exact film specifications.</p>		